Pushing, Sweeping, Scraping!

for house & farm



TUCH





Handy, efficient and powerful!

A stable rod steering and big field tyres ensure a great performance. Basic equipment incl. hydraulic drive and hydraulic connections for further attachments, which can be tool-free mounted or dismounted.

technical data	
engine	Honda gasoline engine, 5,5 HP
wheel drive	hydraulic forward / backwards
speed regulation steps	1 (incl. infinitely variable speed adjustment on enquiry)
total weight	680 mm (for manure scraper)
hydraulic connections	1 x double-acting

Measurements and weights are approx. and non-binding.

options

- ontinuous variable traction drive, up to 3,7 km/h
- Extra broad field tyres
- Manure scraper, V-shape, 100 cm / height 20 cm, type double-lip, incl. level compensation, fully galvanized, incl. ammoniac-resistant wear lip – ensures a quick and simple cleaning of slatted floors, even in tight spaces.
- Fodder blade, 110 cm / height 40 cm, angling right/left, incl. level compensation, powder-coated, incl. highly resistant lip to push the fodder back to the trough and to clean the feed alleys.
- Snow blade, 95 cm, height 40 cm, angling right/left, incl. resistant wear lip, incl. levelling, powder-coated.
- Axial sweeper, 75 cm, hydraulic drive, brush diameter 320 mm, powder-coated, angling right / left, incl. levelling
- Dirt collector, 75 cm, powder-coated, suitable for axial sweeping-machine, incl. scraper lip.
- **Radial sweeper**, ø 80 cm, powder-coated, hydraulically driven, incl. right/left run.





Double-lip manure scraper incl. levelling and interceptors Various mounting possibilities and applications Hitch system and double-acting hydraulic connector, standard

Height adjustable guiding-rod incl. forward/backwards gear

Tuchel Maschinenbau GmbH • Holsterfeld 15 • D-48499 Salzbergen • Phone: +49 (0) 5971 9675-0 • Fax: +49 (0) 5971 9675-30 • E-mail: export@tuchel.com • www.tuchel.com