Cleanly "tucheled"!



For small tractors, communal vehicles & small loaders!









Clean sidewalks, squares and roads quite simply!

The **KOMPAKT** PTO-sweeper has been developped in particular for your compact tractor or communal vehicle. 100% PP brush discs in honeycomb shape (Ø 520 mm) stand for high durability! The **KOMPAKT** can be used for summer and winter services. The user-friendly adjusting-lever allows a smooth adjustment of the brush. The basic configuration of this sweeper includes optionally PTO-drive via PTO-shaft or hydraulic drive. Another item of basic equipment is the mechanical angling. Whether simple sweeping or sweeping with hopper, the hopper does not have to be dismounted.

Technical data	135	150	175	200
Working width (straight/angled) cm	135/ 127	150/ 141	175/ 165	200/ 188
Brush ø mm	520	520	520	520
Total width cm	156	171	196	221
Required oil flow. (at 160 bar) l/min.	25	25	30	30
Weight simple sweeping* kg	185	193	205	218
Weight incl. hopper* kg	240	251	269	287
Fill capacity I	145	161	187	213

^{*} incl. A-frame CAT communal

Options

- Large hopper incl. hydraulic tip, 3rd wheel and PU-lip (to avoid side-slip of stonelets)
- High-fill flap to increase fill-capacity of hopper (+ 30% approx.)
- PTO-shaft
- Hydraulic drive
- Mixed brush (50% wire / 50% PP) or snow brush
- Water-spray system, incl. water-pump and 100 l tank (for rear-mounting via three-point linkage) or directly on the machine
- Hydraulic angling (1 additional double-acting hydraulic drive circuit required)
- Hydraulic side brush, adjustable (for corner sweeping)
- 3rd support-wheel incl. heigh adjustment, for simple sweeping
- Splash guard for winter service
- Reinforced wheels ø 200 x 50 mm for hard work
- Road traffic equipment (prescribed to drive on public roads)
- Extra colour shade

Hitch systems

- A-frame
- Three-point linkage
- Front mower hitch (direct mounting)
- Quick hitch for Tuchel-Trac TRIO
- Quick hitch for yard loaders, small wheel loaders or municipal vehicles incl. 3D floating systems.



Side brush incl. speed adjustment



Double levelling incl. hydraulic angling



Adjusting-lever and parking stand



Simple sweeping mode (standard)

Measurements and weights are approx. and non-binding