

Small - Compact - Flexible.

TUCHEL-TRAC MINI 2

For the
maintenance of
stables &
properties



TUCHEL
MASCHINENBAU GmbH

A true vehicle miracle!

Small, compact, flexible and fast, that's our new **MINI 2**. Standard equipment includes hydrostatic front-wheel drive. The rear steering axle of the MINI 2 enables a turning radius of just 490 mm. Thanks to the quick-hitch system, the mounting and dismounting of various tools is particularly user-friendly. Thus, many jobs around your farm can be done comfortably and quickly.

The main features at a glance:

- Hour meter
- Splash-proof ignition lock
- Robust steering, mechanically via gear ring and steering linkage
- Quick-hitch (Exchange of tools from driver's position possible)
- Tool-less seat adjustment
- Easy accessible engine for maximum ease of maintenance
- Clearly arranged controls
- Steering wheel with integrated steering knob
- Ergonomically shaped foot pedal for the traction drive
- Self-tightening V-belt for the traction drive
- Comfortable getting on and dismounting from the vehicle

Options:

- Slurry scraper 105 cm, V-shaped, wear-resistant PU-double-lips (polyurethane)
- Slurry scraper 105 cm (as described above) incl. side brush \varnothing 600 mm, 100% PP, hydr. swiveling, height is mechanically adjustable (only for H)
- Bedding tool, volume 48 litres, for materials such as: sawdust, straw meal, lime
- Fodder push blade / snow blade 135 cm, right and left swiveling, incl. wear-resistant clearing lip; to lay fodder and to clean the feed table simultaneously, applicable

Technical data		MINI 2 M
Dimensions (without tool)	mm	830 x 1680 x 1260 (width x length x height)
Motor / Capacity		Briggs & Stratton Series 950E 4,9 kW (6,6 HP / 3600 rpm) E-Starter and reversing starter
Drive		hydrostatic front-wheel drive via V-belt
Lifting system		mechanical
Hydraulic connections		---
Weight	kg	250
Turning radius (inside)	mm	490

Technical data		MINI 2 H
Dimensions (without tool)	mm	830 x 1680 x 1260 (width x length x height)
Motor / Capacity		Honda GXV 340 6,6 kW (9 HP / 3600 rpm) E-Starter and reversing starter
Drive		hydrostatic front-wheel drive via V-belt
Lifting system		hydraulic
Hydraulic connections		1 x double-acting (9,8 l / 180 bar)
Weight	kg	280
Turning radius (inside)	mm	490

Measurements and weights are approx. and non-binding.

also for snow clearance

- Fodder push blade / snow blade 135 cm (equipment as described above) incl. hydr. lateral adjustment (only for H)
- Radial brush 105 cm, 100% PP, hydraulic, clockwise / anti-clockwise rotation (only for H)
- Radial brush 105 cm (equipment as described above) incl. deflector plate, for a thorough cleaning of the feed alley (only for H)
- Weed brush \varnothing 750 mm, mechanical adjustment (only for H)



Parking brake



Clearly arranged controls



Weed brush \varnothing 750 mm



Ergonomically shaped foot pedal for the traction drive