

The King of snow!

TUCHEL-SNOW
SF

for
wheel- /
telescopic loaders,
tractors, fork-lifts
& communal
vehicles



TUCHEL
MASCHINENBAU GmbH

Take this and you'll do well!

Standard equipment of the **SF** snow blade includes spring flap segments, which assure a quick clearing of snow. The integrated protection system prevents the snow blade, if it strikes a barrier. The **SF** can be equipped with a PU-lip (polyurethane), a highly resistant communal lip, which guarantees long durability and excellent sliding qualities and a steel lip. Height adjustment of the clearing lip is done by the wheels. Heavy-duty wheels in order to avoid marks on road surfaces are available on option.

options

- hydraulic angling (1 additional double-acting hydraulic drive circuit required); on demand incl. pressure limit valve
- pressure retention valve
- skids
- CSE-wheels (heavy-duty) ø 310 x 105 mm
- snow-guide cloth
- road traffic equipment (warning flags & -holders, side-marker lamps LED)
- colour option

technical data		250	275	300	325	350
total width	cm	250	275	300	325	350
clearing width (in straight & angled position)	cm	250/ 215	275/ 237	300/ 258	325/ 280	350/ 301
weight*	kg	467	497	522	547	572
height	cm	108				
angling	degree	bis 30				

* without hitch system

Measurements and weights are approx. and non-binding.

hitch systems

- Three-point linkage
- A-frame
- Attachment plate incl. lifting-device
- Fork-tine attachment
- Wheel loader-/telly handler hitch

The main features at a glance:

- interceptors on both sides included in standard equipment
- spring flap segments (anti-icing)
- optimum angle of inclination of the clearing lip, for perfect snow clearing
- edge bending (side and top) ensures high stability of the snow blade
- Reinforced pivoting-cylinders



highly wear-resistant communal lip



Hitch systems for various carrier-vehicles available



Height adjustable wheels



Heavy-duty wheels