

# Effective weed removal!

## TUCHEL-SWEEP

WB 750

For wheel loaders, tractors, yard loaders, small communal vehicles & excavators up to 6 t



**TUCHEL**  
MASCHINENBAU GmbH

# Environmentally friendly and thoroughly!

The new hydraulically driven weed brush for wheel loaders, tractors, small communal vehicles and excavators allows you to remove any kind of weed, very easy and effortless, and free of chemicals.

The disc brush has a diameter of 750 mm and is equipped with flat wire bunches, so that even stubborn dirt is no longer an obstacle.

To ensure removal even in edge areas, the weed brush is equipped with a mechanical lateral displacement.

Through manually adjusting the tilt angle, you can achieve the highest possible scratch effect.

Part of the basic equipment is also an adjustable rubber protection cloth which prevents stones and debris flying around uncontrollably.

## Options

- Rope wire bunches, plastic covered, screwable
- Hydr. inclination adjustment of the brush (1 additional double-acting control circuit necessary)
- Hydr. lateral displacement by 450 mm (1 additional double-acting control circuit necessary)
- Guide wheel / support wheel Ø 200 x 50 mm (for < 0,4 m<sup>3</sup> bucket capacity)
- Extra strong castor for guide wheel Ø 250 x 80 mm (for > 0,4 m<sup>3</sup> bucket capacity)
- Throttle valve for speed regulation
- Electro-magnetic switching 12 V, for vehicles with only one double-acting hydraulic control circuit
- Electro-magnetic switching 12 V, for vehicles with two double-acting hydraulic control circuits
- Extra colour shade

Technical data		
Disc brush ø	mm	750
Brush type		Flat wire bunches
Direction of rotation		right / left
Motor		Danfoss OMS Hydr.-Motor
Required oil flow		20 l / min at 180 bar
Lateral displacement (not for excavators)		Mechanical by 450 mm
Rubber protection cloth		Included

Measurements and weights are approx. and non-binding.

## Hitch systems

- Quick-hitch MS01 / MS03 for mini excavators with max. operating weight up to 6 t
- Three-point linkage CAT I / II
- A-frame CAT Communal / 0 / I
- Yard loader attachment
- Wheel loader attachment (up to 0,8 m<sup>3</sup> bucket capacity)
- Attachment for communal vehicles



Height adjustable support wheel

Plastic covered rope wire bunches

Telescopic, with hydr. inclination adjustment

Hydr. telescoping